


**415CO**
**Cilindrische spiraalboren korte uitvoering, staal HSS-CO 5% geslepen**
**DIN 338 ISO 235**
 $R \leq 1200 \text{ N/mm}^2$ 
 $HV \sim 800 \div 860$ 

|  | art.        | L1<br>mm | L<br>mm | Ø<br>mm |
|---|-------------|----------|---------|---------|
| 004150310   | 415CO 1,0   | 12       | 34      | 1,00    |
| 004150312   | 415CO 1,50  | 18       | 40      | 1,50    |
| 004150314   | 415CO 2,00  | 24       | 49      | 2,00    |
| 004150316   | 415CO 2,50  | 30       | 57      | 2,50    |
| 004150320   | 415CO 3,00  | 33       | 61      | 3,00    |
| 004150322   | 415CO 3,50  | 39       | 70      | 3,50    |
| 004150324   | 415CO 4,00  | 43       | 75      | 4,00    |
| 004150326   | 415CO 4,50  | 47       | 80      | 4,50    |
| 004150328   | 415CO 5,00  | 52       | 86      | 5,00    |
| 004150330   | 415CO 5,50  | 57       | 93      | 5,50    |
| 004150332   | 415CO 6,00  | 57       | 93      | 6,00    |
| 004150334   | 415CO 6,50  | 63       | 101     | 6,50    |
| 004150336   | 415CO 7,00  | 69       | 109     | 7,00    |
| 004150338   | 415CO 7,50  | 69       | 109     | 7,50    |
| 004150340   | 415CO 8,00  | 75       | 117     | 8,00    |
| 004150342   | 415CO 8,50  | 75       | 117     | 8,50    |
| 004150344   | 415CO 9,00  | 81       | 125     | 9,00    |
| 004150346   | 415CO 9,50  | 81       | 125     | 9,50    |
| 004150348   | 415CO 10,00 | 87       | 133     | 10,00   |
| 004150350   | 415CO 10,50 | 87       | 133     | 10,50   |
| 004150352   | 415CO 11,00 | 94       | 142     | 11,00   |
| 004150356   | 415CO 12,00 | 101      | 151     | 12,00   |
| 004150360   | 415CO 13,00 | 101      | 151     | 13,00   |

