


78BA-AS
Vonkvrije ringslagsleutels in engelse maten

- Afmetingen in inches

		art.		L mm	Ø mm	S mm	Wt g
	000780908	78BA-AS 11/16	11/16	145	32,0	12,0	210
	000780909	78BA-AS 3/4	3/4	145	32,0	12,0	200
	000780935	78BA-AS 7/8	7/8	155	38,0	13,0	245
	000780936	78BA-AS 15/16	15/16	165	42,0	14,0	250
*	000780937	78BA-AS 31/32	31/32	165	42,0	14,0	250
	000780938	78BA-AS 1'	1	175	46,0	16,0	350
*	000780939	78BA-AS 1.1/16	1.1/16	175	46,0	16,0	350
	000780940	78BA-AS 1.1/8	1.1/8	180	50,0	16,0	455
	000780941	78BA-AS 1.3/16	1.3/16	185	50,0	16,0	475
	000780910	78BA-AS 1.1/4	1.1/4	177	54,0	23,5	570
*	000780954	78BA-AS 1.5/16	1.5/16	200	55,0	18,0	755
*	000780911	78BA-AS 1.3/8	1.3/8	205	58,0	19,0	560
	000780912	78BA-AS 1.7/16	1.7/16	208	60,0	26,5	780
*	000780913	78BA-AS 1.1/2	1.1/2	215	61,0	19,5	790
*	000780947	78BA-AS 1.9/16	1.9/16	225	64,0	20,0	755
*	000780962	78BA-AS 1.11/16	1.11/16	225	64,0	20,0	755
	000780914	78BA-AS 1.5/8	1.5/8	225	67,0	26,0	950
*	000780963	78BA-AS 1.3/4	1.3/4	235	73,0	22,0	1020
	000780916	78BA-AS 1.13/16	1.13/16	243	74,0	28,0	1235
	000780915	78BA-AS 1.7/8	1.7/8	235	73,0	22,0	990
	000780918	78BA-AS 2	2	254	78,0	28,5	1500
	000780920	78BA-AS 2.3/16	2.3/16	264	84,0	30,0	1685
	000780922	78BA-AS 2.3/8	2.3/8	275	91,5	30,0	1960
*	000780924	78BA-AS 2.9/16	2.9/16	286	99,5	31,5	2400
*	000780926	78BA-AS 2.15/16	2.15/16	311	112,5	33,5	3110
*	000780928	78BA-AS 3.1/8	3.1/8	325	118,0	35,5	3500
*	000780930	78BA-AS 3.1/2	3.1/2	355	130,0	39,0	4600



Wrenches subjected to heat treatments should be used with care and attention to avoid any damage to the workpiece.
 Condizioni per l'uso: non usare il cuneo per forare o incidere il metallo.
 Do not use the wedge to drill or cut metal.
 Applications: use with the upper of the tool without any wedge, insert or any other application.

