

TECHNISCHE DATA

- veiligheidsfactor: 6
- warmtebehandeling: normaliseren
- traceerbaarheidscode


LABORATORIUM TESTEN

- chemische analyse
- metallografische analyse
- trekproef

BESCHIKBARE CERTIFICATEN

- Technische productspecificaties
- Testrapport UNI EN10204 type 2.2
- Keuringscertificaat UNI EN10204 type 3.1
- CE-verklaring van overeenstemming



| |  | art. | Ø mm | h mm | WLL kg | E mm |
|---|---|-------------|---------|---------|-----------|---------|
| * | 080400406 | 8040EZ M6 | M6 | 1 | 90 | 11 |
| | 080400408 | 8040EZ M8 | M8 | 1,25 | 140 | 13 |
| | 080400410 | 8040EZ M10 | M10 | 1,5 | 230 | 17 |
| | 080400412 | 8040EZ M12 | M12 | 1,75 | 340 | 20,5 |
| * | 080400414 | 8040EZ M14 | M14 | 2 | 480 | 20,5 |
| | 080400416 | 8040EZ M16 | M16 | 2 | 700 | 27 |
| * | 080400418 | 8040EZ M18 | M18 | 2,5 | 930 | 27 |
| | 080400420 | 8040EZ M20 | M20 | 2,5 | 1200 | 30 |
| * | 080400422 | 8040EZ M22 | M22 | 2,5 | 1450 | 30 |
| | 080400424 | 8040EZ M24 | M24 | 3 | 1800 | 36 |
| * | 080400427 | 8040EZ M27 | M27 | 3 | 2400 | 41 |
| | 080400430 | 8040EZ M30 | M30 | 3,5 | 3200 | 45 |
| * | 080400433 | 8040EZ M33 | M33 | 3,5 | 3900 | 54 |
| * | 080400434 | 8040EZ M33F | M33F | 2 | 3900 | 54 |
| | 080400436 | 8040EZ M36 | M36 | 4 | 4600 | 54 |
| * | 080400437 | 8040EZ M36F | M36F | 3 | 4600 | 54 |
| | 080400442 | 8040EZ M42 | M42 | 4,5 | 6300 | 63 |
| * | 080400443 | 8040EZ M42F | M42F | 3 | 6300 | 63 |
| | 080400448 | 8040EZ M48 | M48 | 5 | 8600 | 68 |
| * | 080400449 | 8040EZ M48F | M48F | 3 | 8600 | 68 |
| | 080400456 | 8040EZ M56 | M56 | 5,5 | 11500 | 78 |
| * | 080400457 | 8040EZ M56F | M56F | 4 | 11500 | 78 |
| | 080400464 | 8040EZ M64 | M64 | 6 | 16000 | 90 |
| * | 080400465 | 8040EZ M64F | M64F | 4 | 16000 | 90 |