

8042EN
Oogmoeren zelf-kleurend

CE

DIN 582
TECHNISCHE DATA

- veiligheidsfactor: 6
- warmtebehandeling: normaliseren
- traceerbaarheidscode


LABORATORIUM TESTEN

- chemische analyse
- metallografische analyse
- trekproef

BESCHIKBARE CERTIFICATEN

- Technische productspecificaties
- Testrapport UNI EN10204 type 2.2
- Keuringscertificaat UNI EN10204 type 3.1
- CE-verklaring van overeenstemming



| |  | art. | Ø mm | $\frac{W}{L}$ mm | WLL kg | F mm |
|---|---|-------------|---------|---------------------|-----------|---------|
| * | 080420306 | 8042EN M6 | M6 | 1 | 90 | 14 |
| | 080420308 | 8042EN M8 | M8 | 1,25 | 140 | 20 |
| | 080420310 | 8042EN M10 | M10 | 1,5 | 230 | 25 |
| | 080420312 | 8042EN M12 | M12 | 1,75 | 340 | 30 |
| * | 080420314 | 8042EN M14 | M14 | 2 | 480 | 30 |
| | 080420316 | 8042EN M16 | M16 | 2 | 700 | 35 |
| * | 080420318 | 8042EN M18 | M18 | 2,5 | 930 | 35 |
| | 080420320 | 8042EN M20 | M20 | 2,5 | 1200 | 40 |
| * | 080420322 | 8042EN M22 | M22 | 2,5 | 1450 | 40 |
| | 080420324 | 8042EN M24 | M24 | 3 | 1800 | 50 |
| * | 080420327 | 8042EN M27 | M27 | 3 | 2400 | 55 |
| | 080420330 | 8042EN M30 | M30 | 3,5 | 3200 | 60 |
| | 080420336 | 8042EN M36 | M36 | 4 | 4600 | 70 |
| * | 080420337 | 8042EN M36F | M36F | 3 | 4600 | 70 |
| | 080420342 | 8042EN M42 | M42 | 4,5 | 6300 | 80 |
| * | 080420343 | 8042EN M42F | M42F | 3 | 6300 | 80 |
| | 080420348 | 8042EN M48 | M48 | 5 | 8600 | 90 |
| * | 080420349 | 8042EN M48F | M48F | 3 | 8600 | 90 |