

ISO 2236

- Kan worden gebruikt met een bedieningsstang die in het gat wordt gestoken.
- Het gat aan de korte kant maakt toegang tot de moer mogelijk, zelfs met uitstekende schroefdraad.

art.	M mm	M1 mm	L mm	L1 mm	Ø mm	Ø1 mm	A mm	A1 mm	h g	
009370006	937 6X6	6	6	110	15	11,5	5	8	15	55
009370007	937 7X7	7	7	116	15	12,5	6	9	18	60
009370008	937 8X8	8	8	120	21	13	6	11	20	65
009370009	937 9X9	9	9	125	21	14	7	11	20	75
009370010	937 10X10	10	10	133	25	16,5	8	13	22	105
009370011	937 11X11	11	11	143	25	17,5	8,5	14	23	125
009370012	937 12X12	12	12	148	25	19	8,5	14	25	165
009370013	937 13X13	13	13	154	34	19,5	9,5	16	28	175
009370014	937 14X14	14	14	167	34	21,5	10	17	28	220
009370015	937 15X15	15	15	182	40	22,5	10	17	29	235
009370016	937 16X16	16	16	193	40	24,5	11	20	33	335
009370017	937 17X17	17	17	198	44	26	12	20	34	340
009370018	937 18X18	18	18	215	44	26,5	13	20	34	370
009370019	937 19X19	19	19	220	48	29	14	22	35	435
009370020	937 20X20	20	20	222	48	30,5	14	22	37	485
009370021	937 21X21	21	21	236	48	30,5	16	25	39	575
009370022	937 22X22	22	22	250	52	32,5	16	25	41	610
009370023	937 23X23	23	23	256	52	33,5	17	26	44	705
009370024	937 24X24	24	24	272	55	35	19	27	46	805
009370025	937 25X25	25	25	282	55	36,5	19	27	47	895
009370026	937 26X26	26	26	296	61	37,5	20	28	47	950
009370027	937 27X27	27	27	296	61	39	21	28	50	1220
009370028	937 28X28	28	28	314	61	39	22	28	51	1235
009370030	937 30X30	30	30	348	70	42,5	23	31	51	1520

